

MARKETAIR, INC.

SUPPLEMENTARY PRICE SHEET

REVISED JULY 6, 2023

EasyPlenum

Prefabricated Plenums for ducted minisplit/VRF/VRV ceiling AC units, molded from expanded sintered Polystyrene.

MODEL	DESCRIPTION	CARTON QTY	LIST PRICE EACH
EPM-3	MINI Universal Plenum – Max Duct size:26" W X 7 1/4" H. 3 X 5" / 6" front collars, 2 X 8" side collars. Height 8.6" – Width 32.2"- Depth 13.6".	1	\$370.00
EPM-4	MINI Universal Plenum – Max Duct size:34" W X 7 1/4" H. 4 X 5" / 6" front collars, 2 X 8" side collars. Height 8.6" – Width 39.7"- Depth 13.6".	1	\$396.00
EPU-2	Universal Plenum – Max Duct size: 24" W X 8 1/2" H. 2 X 6" / 8" front collars, 2 X 8" side collars. Height 9.6" – Width 29.2"- Depth 13.7".	1	\$382.00
EPU-3	Universal Plenum – Max Duct size: 34" W X 8 1/2" H. 3 X 6" / 8" front collars, 2 X 8" side collars. Height 10.4" – Width 39.4"- Depth 13.7".	1	\$412.00
EPU-4	Universal Plenum – Max Duct size: 44" X 9 1/4". 4 X 6" / 8" front collars, 2 X 8" side collars. Height 11.2" – Width 49.7"- Depth 13.7".	1	\$446.00
EPU-5	Universal Plenum – Max Duct size: 53" W X 10" H. 5 X 6" / 8" front collars, 2 X 8" side collars Height 12" – Width 59.9"- Depth 13.7".	1	\$480.00

Material: Graphite infused sintered expanded Polystyrene

Thermal Conductivity : 0.0030/0.033 W/mK

Vapor Resistance : 40/70 μ

Operating Temperature : -30 to +90° C = -22°F to 194°F

Water Absorption : % volume < 5

Euroclass Fire Rating : Class E / Class 2

Heat Performance : SP .30mm 0.95 m2K/W

COUNTRY OF ORIGIN: Italy

NOTE: EASYPLENUMS are not subject to our standard freight policy, these are prepay & add

EASYPLENUMS ARE NOW INVENTORY ITEMS - LEAD TIME IS 3-4 days from our New Jersey office